



0605 Screw pitch gauges



☒	☒	Measuring range mm	Number of devices	Description	Order no.
		0.25 - 6	24	Metric threads according to ISO	0605 101
		0.4 - 7	20	Combined metric threads according to SI System	0605 102
		4 - 62	28	Whitworth threads according to DIN	0605 103
		8 - 28	6	Whitworth pipe threads	0605 104
		0.4 - 7.0 / 4 - 62	48	Combined metric SI and Whitworth threads	0605 105
		0.25 - 6.00 / 4 - 62	52	Combined metric and Whitworth	0605 106
		0.25 - 6.00 / 4 - 62 / 8 - 28	58	Metric Whitworth and pipe threads	0605 107
		4 - 42	30	US - threads	0605 108
		10 - 40	14	US - threads SAE	0605 109
		4 - 64	22	UNC - threads	0605 110
		12 - 80	16	UNF - threads	0605 111
		4 - 26	20	BSF - threads	0605 112

0606 / 0607 Feeler gauges



0606 121



0607 201



0607 401

Model

- Conical blades
- Width 10mm
- Blade length 100
- Locking nut

☒	☒	Measuring range mm	Number of blades	Order no.
Spring band steel				
		0.03 - 0.1	8	0606 121
		0.05 - 0.5	8	0606 123
		0.05 - 1	13	0606 127
		0.05 - 1	20	0606 130
		0.1 - 2	20	0606 131
		0.1 - 0.5	21	0606 132
		0.05 - 2	21	0606 133
		0.03 - 1	32	0606 136
Stainless spring band steel				
		0.05 - 0.5	8	0607 201
		0.05 - 1	13	0607 202
		0.05 - 1	20	0607 203
Brass (anti-magnetic)				
		0.05 - 0.5	8	0607 401
		0.05 - 1	13	0607 402
		0.05 - 1	20	0607 403



0606 Feeler gauges, long version



Model

- Cylindrical blades
- Width 13 mm

		Measuring range mm	Length mm	Number of blades	Order no.
		0.05 - 0.5	150	8	0606 150
		0.05 - 0.5	200	8	0606 152
		0.05 - 0.5	300	8	0606 154
		0.05 - 1	200	13	0606 160
		0.05 - 1	300	13	0606 162
		0.05 - 1	200	20	0606 170
		0.05 - 1	300	20	0606 172
		0.1 - 2	200	20	0606 176
		0.1 - 2	300	20	0606 178

0608 Feeler gauge



NEW

Model

- Conical blade
- Width 10 mm

		Measuring range mm	Number of blades	Order no.
		0.1 - 0.4	6	0608 140
		0.05 - 1	13	0608 143
		0.05 - 1	20	0608 144
		0.03 - 1	32	0608 149