



Tipuri de vaselina standard si accesorii

VASELINA	NLGI	Agent de ingrosare	Interval de temperatura	Vascozitate la 40 °C	Aplicatii						
					Rulmenti cu role	Lagare de alunecare	Ghidaje liniare	Angrenaje/ Roti dintate	Surub conductor	Arbore de antrenare	Lanturi
SL01 Rezistenta la apa, vaselina pe termen lung	2	Litiu-calcium	-30 °C pana la 120 °C	118	+	+	•	•	+	+	-
SL02 Vaselina de inalta performanta cu MoS ₂	2	Litiu	-25 °C pana la 130 °C	270	•	+	-	+	-	-	-
SL04 Vaselina pentru temperatura ridicata pentru lubrifiere pe termen lung (EP)	2	Anorganic agent de ingrosare	-20 °C pana la 160 °C	540	+	•	-	•	•	-	-
SL06 Rezistenta la apa, vaselina fluida (EP)	0	Litiu-calcium	-20 °C pana la 120 °C	150	+	+	+	+	•	-	-
SL09 Vaselina universala, usor biodegradabila	2	Litiu-calcium	-20 °C pana la 100 °C	100	+	+	•	•	-	-	-
SL10 Vaselina speciala pentru industria alimentara, a bauturilor si industria farmaceutica	2	Complex de aluminiu	-30 °C pana la 140 °C	350	+	+	•	+	•	-	-
SL24 Vaselina pentru o gama larga de temperaturi (EP)	2	Complex de litiu	-30 °C pana la 140 °C	185	+	+	•	•	+	+	-
SL25 Vaselina poliuree pentru temperaturi ridicate	2	Poliuree	-20 °C pana la 160 °C	110	+	•	-	•	•	-	-
SL26 Vaselina complexa sulfonate de calciu (EP)	1,5	Complex de calciu	-20 °C pana la 150 °C	460	+	+	-	•	•	-	-

+ recomandat • posibil - nu se recomanda



**TOM's
TIP**

Specificatii tehnice sunt disponibile pentru toate tipurile de vaselina si ulei pe www.simatec.com/en/lubricants

