

Carbon Filter VACUMAT

Also in
ATEX-version
available!



VACUMAT 2200

Areas of application

- » Improving indoor air quality by reducing or removing unpleasant odours
- » Adsorption of gaseous environmental pollutants
- » For single and multi-location separation



Ideal for

Gaseous odors and pollutants

Slight chemical exposure

Sonderausführungen

- » **NEU** ATEX-Ausführung auf Anfrage
- » Stationäre Ausführung
- » Sonderlackierung
- » Weitere Ausführungen auf Anfrage



Control panel with operating hour meter



Active charcoal filter



VACUMAT for aspiration at a workplace

ESTAPLUS

Special features

- » Effective pre-filter system for separating coarse particles for a long filter service life spans of the main filter
- » Active charcoal filter cell with active charcoal granulate for effective odour filtering
- » For connection to extraction arm, cover or pipe
- » Mobile and space-saving design

Your benefits

- » High-performance 2-level filter system
- » Low operating noise
- » Low operating costs
- » Operating hour counter for monitoring filter service life

Technical Data

VACUMAT		1000	2200
Max. Airflow	m ³ /h	1.010	2.250
Max. negative pressure	Pa	1.250	2.550
Intake diameter	mm	150	200
Voltage	V	400	400
Motor	kW	1.1	2.2
Mass of active charcoal	kg	25	25
Dimensions (L/W/H)	mm	1.050 × 800 × 1.330	1.050 × 800 × 1.330
Weight	kg	215	218
Sound emission	dB(A)	62	71
Order Number		07100	07220

Dust Extractors

High Vacuum
Extraction Units

Welding Fume
Filters

Oil Mist
Separators

Carbon Filter

Downdraft
Tables

Extraction Fans

Extraction Arms

Filter Towers

Central Extraction
Systems

Pipe Systems