

CRP CBP CGP

INSULATED CHAIN TERMINALS

CP range with easy entry - for Copper conductors




The "CP" range of terminals has been designed to meet the increasing demands for improved safety and reliability of electrical connectors. Developed for use with production equipment, to give a quick and reliable

crimped joint, the Polycarbonate insulation is a Halogen free, self-extinguishing thermoplastic material class V0 (UL 94).

The unique funnel shaped entry of the insulation sleeve guarantees to

tal insertion of the conductor strands into the terminal barrel, creating a secure and reliable, electrical and mechanical connection.


The operating temperature range is -20 to +115°C (Surge +130°C).




Certified according to EN 45545-2:2013



pin terminals




blade terminals



| Conductor Size sqmm (AWG) | Type | Dimensions mm | | | | Quantity |
|---------------------------|---------|---------------|-----|------|------|----------|
| | | Ø | B | P | L | |
| 0,25÷1,5 (22÷16) | CRP-P8 | 4,0 | 1,6 | 8,0 | 17,9 | 2.000 |
| | CRP-P10 | 4,0 | 1,6 | 10,0 | 19,9 | 2.000 |
| | CRP-P12 | 4,0 | 1,6 | 12,0 | 22,1 | 2.000 |
| 1,5÷2,5 (16÷14) | CBP-P8 | 4,9 | 1,8 | 8,0 | 17,9 | 1.750 |
| | CBP-P10 | 4,9 | 1,8 | 10,0 | 19,9 | 1.750 |
| | CBP-P12 | 4,9 | 1,8 | 12,0 | 21,9 | 1.750 |
| 4÷6 (12÷10) | CGP-P10 | 6,6 | 2,2 | 10,0 | 24,5 | 1.250 |
| | CGP-P12 | 6,6 | 2,2 | 12,0 | 26,7 | 1.250 |
| | CGP-P14 | 6,6 | 2,2 | 14,0 | 28,7 | 1.250 |


| Conductor Size sqmm (AWG) | Type | Dimensions mm | | | | Quantity |
|---------------------------|--------------|---------------|-----|------|------|----------|
| | | Ø | B | P | L | |
| 0,25÷1,5 (22÷16) | CRP-PP12 | 4,0 | 3,0 | 12,8 | 22,9 | 2.000 |
| | CRP-PP12/1* | 4,0 | 3,0 | 11,3 | 21,4 | 2.000 |
| | CRP-PP12/23* | 4,0 | 2,3 | 13,2 | 23,3 | 2.000 |
| 1,5÷2,5 (16÷14) | CRP-PP14 | 4,0 | 3,0 | 14,8 | 24,9 | 2.000 |
| | CBP-PP12 | 4,9 | 3,5 | 12,8 | 22,9 | 1.750 |
| 4÷6 (12÷10) | CBP-PP12/25* | 4,9 | 2,5 | 13,3 | 23,4 | 1.750 |
| | CGP-PP12 | 6,6 | 4,0 | 13,3 | 27,4 | 1.250 |
| | CGP-PP17* | 6,6 | 2,9 | 19,1 | 33,2 | 1.250 |

male disconnect terminals




| Conductor Size sqmm (AWG) | Type | Tab Size mm | Quantity |
|---------------------------|----------|-------------|----------|
| 0,25÷1,5 (22÷16) | CRP-M608 | 6,35 x 0,8 | 2.000 |
| | CBP-M608 | 6,35 x 0,8 | 1.750 |
| 4÷6 (12÷10) | CGP-M608 | 6,35 x 0,8 | 1.250 |

female disconnect terminals



| Conductor Size sqmm (AWG) | Type | Tab Size mm | Quantity |
|---------------------------|-----------------|-------------|-----------|
| 0,25÷1,5 (22÷16) | CRP-F305 | 2,8 x 0,5 | 2.000 |
| | CRP-F308 | 2,8 x 0,8 | 2.000 |
| | CRP-F405 | 4,8 x 0,5 | 2.000 |
| | CRP-F408 | 4,8 x 0,8 | 2.000 |
| | CRP-F608 | 6,35 x 0,8 | 2.000 |
| | 1,5÷2,5 (16÷14) | CBP-F405 | 4,8 x 0,5 |
| CBP-F408 | | 4,8 x 0,8 | 1.750 |
| CBP-F608 | | 6,35 x 0,8 | 1.750 |
| 4÷6 (12÷10) | CGP-F608 | 6,35 x 0,8 | 1.250 |

female disconnect terminals fully insulated



| Conductor Size sqmm (AWG) | Type | Tab Size mm | Quantity |
|---------------------------|------------|-------------|----------|
| 0,25÷1,5 (22÷16) | CRP-F405P* | 4,8 x 0,5 | 2.000 |
| | CRP-F408P* | 4,8 x 0,8 | 2.000 |
| | CRP-F608P* | 6,35 x 0,8 | 1.500 |
| 1,5÷2,5 (16÷14) | CBP-F408P* | 4,8 x 0,8 | 1.500 |
| | CBP-F608P* | 6,35 x 0,8 | 1.500 |
| 4÷6 (12÷10) | CGP-F608P | 6,35 x 0,8 | 1.250 |