

MAXIBLOCK CABLE GLANDS

Polyamide PA6.6

MAXIblock®

standard, factory fitted with Polyethylene foam discs

Metric thread M 1.5 pitch CEI EN 60423 CEI EN 62444

Type	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1900DP.M12	M12x1,5	12,2	3,5- 7	15	8	18-22	100/10
1900DP.M16	M16x1,5	16,2	5 -10	19	8	22-27	100/10
1900DP.M20	M20x1,5	20,5	7 -13	25	9	24-30	50/10
1900DP.M25	M25x1,5	25,4	10 -17	30	10	28-39	30/10
1900DP.M32	M32x1,5	32,5	13 -21	36	10	33-44	20/10
1900DP.M40	M40x1,5	40,5	19 -28	46	10	36-45	10/5
1900DP.M50	M50x1,5	50,5	27 -35	55	12	43-52	10/5
1900DP.M63	M63x1,5	64,0	34 -45	66	12	45-55	5/5


Pg thread DIN 40 430

Type	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1900DP.07	Pg 7	12,7	3,5- 7	15	8	18-22	100/10
1900DP.09	Pg 9	15,5	5 - 8	19	8	22-26	100/10
1900DP.11	Pg11	18,8	5 -10	22	8	23-28	100/10
1900DP.13	Pg13,5	20,5	7 -12	24	9	24-29	50/10
1900DP.16	Pg16	22,6	10 -14	27	10	26-31	30/10
1900DP.21	Pg21	28,5	13 -18	33	12	30-35	20/10
1900DP.29	Pg29	37,2	18 -25	42	12	33-39	20/10
1900DP.36	Pg36	47,2	20 -32	53	14	42-49	10/5
1900DP.42	Pg42	54,2	28 -38	60	14	42-50	5/5
1900DP.48	Pg48	60,0	37 -45	66	15	45-55	5/5

1900DP



Material: POLYAMIDE PA6.6
self-extinguishing class V2 (UL 94)
Temperature range:
-20°C to +90°C (continuous)
Sealing ring: NEOPRENE® 50 sh A
Protection: IP 68
Colour: RAL 7035 light grey
Discs: 2 mm thick Polyethylene foam



MAXIBLOCK CABLE GLANDS

Polyamide PA6.6

BSP thread ISO 228/1

Type Light Grey	P	Fixing Hole Ø (mm)	Ø A min-max (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity
1900.14	G1/4"	13,5	3- 6,5	15	8	18-22	100
1900.38	G3/8"	17,0	4- 8	19	8	22-26	100
1900.12	G1/2"	21,5	7-12	24	10	24-29	100
1900.34	G3/4"	27,0	13-18	33	12	30-35	50

Add to Ref: N for Black

Material: POLYAMIDE PA6.6
self-extinguishing class V2 (UL 94)
Temperature range:
-20°C to +90°C (continuous)
Sealing ring: NEOPRENE® 50 sh A
Protection: IP 68
Colour: RAL 7035 light grey,

1900

