


# 1700

## ENTRY BUSHES

Polyamide PA6



Material: POLYAMIDE PA6  
 self-extinguishing class V0 (UL 94)  
 Temperature range:  
 -20°C to +90°C (continuous)  
 Colour: RAL 7035 light grey,  
 RAL 9005 black



### Entry bushes

#### Pg thread DIN 40 430 - Dimensions DIN 46 320

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1700.2*	Pg 9	10,0	16	9,0	14,0	600/100
1701.2*	Pg11	11,5	19	10,0	15,0	300/100
1702.2*	Pg13,5	13,5	21	11,0	16,5	300/100
1703.2	Pg16	16,0	23	12,5	18,5	200/100
1704.2	Pg21	22,0	30	12,0	17,5	100/50
1705.2	Pg29	27,0	40	15,0	22,0	

#### BSP thread ISO 228/1

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1830*	G1/4"	8,5	15	8,5	13,5	800/100
1831*	G3/8"	11,5	17	9,0	14,0	300/100
1832*	G1/2"	13,0	21	11,0	16,5	300/100

#### Metric thread M 1.5 pitch CEI EN 60423

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
Δ 1835G	M16x1,5	11,5	17	9	14,0	100/100
1836*	M20x1,5	13,5	21	11	16,5	300/100

\*Add to Ref: N for Black

Δ Dark Grey only

### Blind entry bushes

#### Pg thread DIN 40 430 - Dimensions DIN 46 320

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1702.5*	Pg13,5	-	21	11,0	17,0	300/100
1703.5	Pg16	-	23	12,5	18,5	200/100

#### BSP thread ISO 228/1

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1861*	G3/8"	-	17	9	14	600/100
1862*	G1/2"	-	21	11	16,5	200/100

#### Metric thread M 1.5 pitch CEI EN 60423

Type Light Grey	P	Ø A (mm)	B Spanner (mm)	C (mm)	L min-max (mm)	Quantity Box/Bag
1866*	M20x1,5	-	21	11	17	100

\*Add to Ref: N for Black

