

MECHANICAL TOOLS CRIMPSTAR® RANGE

HN-A25

for uninsulated terminals and connectors A-M, L-M and L-P series

Crimpstar®



TECHNICAL FEATURES

Crimping Range	Uninsulated terminals and connectors A-M, L-M and L-P series for conductor sizes 10 to 25 sqmm	
Dimensions mm		
Length	229	
Width	78,6	
Height	18,3	
Weight g	500	
Package Dimensions	240 x 81 x 25	



Manual tool, compact and easy to use, equipped with:

- treated steel crimp jaws with high mechanical properties.
- factory-set ratchet for crimping control (automatic handle opening upon completion of crimping operation).

- Emergency release lever which, if necessary, opens the crimp jaws before their complete closure.
- Ergonomically designed non-slip moulded plastic grips.

MECHANICAL TOOLS CRIMPSTAR® RANGE

HN-D25

for Cu tube lugs DR (DIN 46235) and through connectors DSV (DIN 46267)

Crimpstar®



TECHNICAL FEATURES

Crimping Range	Cu tube lugs DR (DIN 46235) and through connectors DSV (DIN 46267) for conductor sizes 10 to 25 sqmm	
Dimensions mm		
Length	229	
Width	78,6	
Height	18,3	
Weight g	500	
Package Dimensions	240 x 81 x 25	



Manual tool, compact and easy to use, equipped with:

- treated steel crimp jaws with high mechanical properties.
- factory-set ratchet for crimping control (automatic handle opening upon completion of crimping operation).

- Emergency release lever which, if necessary, opens the crimp jaws before their complete closure.
- Ergonomically designed non-slip moulded plastic grips.