

KTS1632

HAND TOOLS

for cutting and sealing flexible plastic conduit



Cuts and seals flexible plastic conduit in a single operation. Lightweight and easy to operate. Suitable for flexible conduits from Ø16 to Ø32 mm.



TECHNICAL FEATURES

Dimensions mm

Length	230
Width	85
Thickness	18
Weight kg	0.82

PC1

for cutting plastic pipe



Plastic pipe cutting tool
Cutting capacity: Ø 6 to Ø 47 mm.



Body: die-cast aluminium alloy
Blade material: hardened Carbon Steel

TECHNICAL FEATURES

Length	200
Width	80
Thickness	18
Weight kg	0.82

MT-FC48N

FRAME-TYPE HOLE PUNCHING TOOL

for cable trunking



Lightweight and easy to operate, designed for punching holes up to 47.2 mm diameter in the side wall of trunking without the need for pre drilling.



VAL-P30
Supplied in a robust plastic case.

Table denotes the punch/die set reference, for each hole size. Suitable for punching holes in mild steel, fibreglass or plastic material, up to 2 mm thick.

Hole Dimensions				Maximum thickness of mild steel (mm)	Type		
Nominal	Ø (mm)	Ø (inch)	Pg				
	15,5	.610	Pg9	-	-	2	RD15.5SS-FC
	16,2	.638	-	ISO-16	-		RD16.2SS-FC
	17,5	.689	-	-	-		RD17.5SS-FC
	18,8	.740	Pg11	-	-		RD18.8SS-FC
	19,1	.752	-	-	-		RD19.1SS
	20,5	.807	Pg 13,5	ISO-20	-		RD20.5SS
	22,6	.890	Pg16	-	-		RD22.6SS
	23,8	.937	-	-	5/8"		RD23.8SS
	25,4	1.000	-	ISO-25	-		RD25.4SS
	27,0	1.063	-	-	3/4"		RD27.0SS
	28,5	1.122	Pg21	-	-		RD28.5SS
	30,5	1.201	-	-	7/8"		RD30.5SS
	31,8	1.252	-	-	-		RD31.8SS
	32,5	1.279	-	ISO-32	-		RD32.5SS
	34,6	1.362	-	-	-		RD34.6SS
	37,2	1.464	Pg29	-	-		RD37.2SS
	38,1	1.500	-	-	-		RD38.1SS
	40,5	1.594	-	ISO-40	-		RD40.5SS-FC
	41,3	1.626	-	-	-		RD41.3SS-FC
	42,5	1.673	-	-	1 1/4"		RD42.5SS-FC
	43,2	1.701	-	-	-	RD43.2SS-FC	
	44,5	1.752	-	-	-	RD44.5SS-FC	
	47,2	1.858	Pg36	-	-	RD47.2SS-FC	