

PORTABLE ELECTRO-HYDRAULIC PUMPS B70M-P24 RANGE

battery operated



Easily accessible oil top-up inlet




Remote electrical hand or foot controller connection (not KV version)



Remote pneumatic hand controller connection (KV version only)



24V dc external power supply socket with protective cap



High pressure hose connects to automatic self-lock quick coupling with protective cap



Battery residual power level display



Manual pressure release button



S:

PORTABLE ELECTRO-HYDRAULIC PUMPS

battery operated

TECHNICAL FEATURES

Operating pressure bar	700
Dimensions mm	
Length	390
width	163
Height	323
Battery	24V 3.1Ah
Weight kg (with Battery)	9,2*

*without accessories



B70M-P24

- 1 Portable electro-hydraulic pump, 24V dc battery for independent use, developing 700 bar pressure; equipped with an integral socket for connection to an external 24 V dc supply
- 2 BH2433 Battery 24V dc 3.1Ah
- 3 DC24 External battery charger
- 4 Shoulder strap
- 5 Canvas holdall for carrying accessories
- 6 3 m flexible hose complete with male + female 3/8" NPT self-lock quick couplers
- 7 ERCH Remote control

TECHNICAL FEATURES

Operating pressure bar	700
Dimensions mm	
Length	390
width	163
Height	323
Battery	24V 3.1Ah
Weight kg (with Battery)	9,2*

*without accessories



B70M-P24-CH

- 1 Portable electro-hydraulic pump, 24V dc battery for independent use, developing 700 bar pressure; equipped with an integral socket for connection to an external 24 V dc supply
- 2 BH2433 Battery 24V dc 3.1Ah
- 3 DC24 External battery charger
- 4 Shoulder strap
- 5 Canvas holdall for carrying accessories
- 6 ERCH-WH Remote hand controller integrated with 3 m length flexible hose complete with male + female 3/8" NPT self-lock quick couplers

TECHNICAL FEATURES

Operating pressure bar	700
Dimensions mm	
Length	390
width	163
Height	323
Battery	24V 3.1Ah
Weight kg (with Battery)	9,2*

*without accessories



B70M-P24-KV

- 1 Portable electro-hydraulic pump, 24V dc battery for independent use. Equipped with high dielectric insulated oil and automatic "insulated" lock quick coupler to allow connection only with insulated hoses.
- 2 BH2433 Battery 24V dc 3.1Ah
- 3 DC24 External battery charger
- 4 Shoulder strap
- 5 Canvas holdall for carrying accessories
- 6 PRCH Remote pneumatic hand controller

Insulated heads suitable for use with this pump are generally supplied complete with high pressure insulated hoses; if necessary the

ACCESSORIES FOR B70M-P24

purchase separately

ESC300CEE

Connecting cable with 24V dc CEE type plug (for power from an external source, length 3 meters)



ESC600

Connecting cable with crocodile clips (for power from an external source, length 6 meters)



BPS230.24

network power supply (not for intensive use)
INPUT 230V ac 50-60Hz; OUTPUT 24V dc
thermal and short circuit protection.
Current supply: up to 4A extended use;
18A for 50 s; 25A for 8 s.



EPS115-230.24

network power supply
SUPPLY IN: 110/240V
ac autorange
50-60Hz; 700W
SUPPLY OUT: 24V dc; 30A max



ERCH-WH

Remote hand controller integrated
with 3 m length flexible hose



TRS-B70

Canvas rucksack
(for carrying the pump)



VAL-P18

Durable transport case for pump and
accessories.



SH-B70

Hook for hanging the pump
from a ladder



RCP-B70

Portable remote foot control

