

18.0 V Cordless hydraulic Frame-Type hole punching tool

B-FC470

general features

MAIN APPLICATIONS

specifically designed to punching holes from 15,5 up to 47,2 mm diameter

TECHNICAL FEATURES

Max hole punch Ø mm	47,2
Max centre of hole to edge of trunking (mm)	53,5
Dimensions mm	
Length	379
Height	346
Width	83
Battery	18.0V 4.0Ah
Weight kg (with Battery)	6,2


STORAGE

Type	VAL-FC470
Dimensions mm L x P	559 x 459 x 131
Weight kg	6,7
	✓
Purchase separately	-



The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- USB cable
- Metal carrying case suitable for storing the tool and accessories



Next generation of 18.0 V cordless hydraulic cutting tool specifically designed to punching holes from 15,5 up to 47,2 mm diameter in the side wall of trunking without the need for pre drilling.

New Li-Ion 18 V 4 Ah batteries offer a higher capacity than 14.4 V 3 Ah, while greater punch speed and punching force result from a revitalised hydraulic system with double speed action.

The battery is equipped with led indicators that indicate the remaining battery life at any time by pressing the adjacent button.

The head can rotate through 180 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables.

Fitted with a maximum hydraulic pressure valve.

Designed with improved balance, B-FC470 is easily manageable during the punching process and, by the use of bi-component plastics, has a shell with high resistance to wear and damage.

Rubber grip inserts, low noise and minimal vibration aid operator comfort while additional convenience and safety are provided by LED lighting of the working area.

Operating temperature: -15 to +50 °C

Also available in the hand operated mechanical version MT-FC48N (see page 132).

Table denotes the punch/die set reference, for each hole size. Suitable for punching holes in mild Steel, fibreglass or plastic material, up to 2 mm thick.

Hole Dimensions				Maximum thickness of mild Steel (mm)	Type
Nominal	Pg	ISO	Inch		
15,5	.610	Pg9	-	2	RD15.5SS-FC
16,2	.638	-	ISO-16		RD16.2SS-FC
17,5	.689	-	-		RD17.5SS-FC
18,8	.740	Pg11	-		RD18.8SS-FC
19,1	.752	-	-		RD19.1SS
20,5	.807	Pg 13,5	ISO-20		RD20.5SS
22,6	.890	Pg16	-		RD22.6SS
23,8	.937	-	5/8"		RD23.8SS
25,4	1.000	-	ISO-25		RD25.4SS
27,0	1.063	-	3/4"		RD27SS
28,5	1.122	Pg21	-		RD28.5SS
30,5	1.201	-	7/8"		RD30.5SS
31,8	1.252	-	-		RD31.8SS
32,5	1.279	-	ISO-32		RD32.5SS
34,6	1.362	-	-		RD34.6SS
37,2	1.464	Pg29	-		RD37.2SS
38,1	1.500	-	-		RD38.1SS
40,5	1.594	-	ISO-40		RD40.5SS-FC
41,3	1.626	-	-		RD41.3SS-FC
42,5	1.673	-	1 1/4"		RD42.5SS-FC
43,2	1.701	-	-	RD43.2SS-FC	
44,5	1.752	-	-	RD44.5SS-FC	
47,2	1.858	Pg36	-	RD47.2SS-FC	