

18.0 V CORDLESS HYDRAULIC CUTTING TOOL

B-TC250BS

overhead line application

MAIN APPLICATIONS

specifically designed to cut Copper, aldrej, Aluminium, Aluminium-Steel cables and Steel ropes, Aluminium and Steel rods having Ø max 26 mm

STORAGE

Type	VAL-P48
Dimensions mm L x W x H	620 x 360 x 138
Weight kg	2,4
	✓
Purchase separately	-



TECHNICAL FEATURES

Max cutting Ø mm	26
Dimensions mm	
Length	436
Height	140
Width	81
Battery	18.0V/2.0Ah
Weight kg (with Battery)	3,4


The tool is supplied as:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- USB cable
- Plastic carrying case suitable for storing the tool and accessories



Can be operated with one hand. Balanced for greater control. Head rotates 180° for ease of operation in confined spaces. The open head and the "scissor" movement of the blades facilitate the cutting of running cables. Fitted with a maximum pressure valve.

CUTTING CAPACITY - a few examples



Section	Ø	Ø	Stranding	Cable Type
mm²	mm	mm		
120	13,3 mm	-	-	RIM120
95	18,5 mm	-	-	Steel cable flex
50	8,9	-	7x2,95 mm	Bronze
70	10,3	-	19 x 2,06 mm	Bronze
95	12,5	-	19 x 2,50 mm	Bronze
70	10,7	-	19/2,14	Aluminium
95	12,5	-	19/2,5	Aluminium
150	15,75	-	37/2,25	Aluminium
323	23,25	-	19/4,65	Aluminium
415	-	26,46	37/3,78	Aluminium
35/6	8,1	-	7/2,70	Aluminium-steel
50/8	9,6	-	7/3,20	Aluminium-steel
50/30	11,7	-	12/2,33+7/2,33	Aluminium-steel
70/12	11,6	-	7/1,45+26/1,80	Aluminium-steel
95/15	13,4	-	7/1,65+26/1,10	Aluminium-steel
150/25	17,3	-	7/2,15+20/2,70	Aluminium-steel
230/30	21,0	-	24/3,5+7/2,33	Aluminium-steel
226	19,5	-	37/2,79	Aluminium-steel
239	20,1	-	37/2,87	Rope Aluminium Alloy
153	16,0	-	19/3,2	Cu
16	9,0	-	126/0,4	Cu flex
70	19,5	-	2214/0,2	Cu extra flex
120	19,9	-	608/0,5	Cu flex
240	-	28,6	1221/0,5	Cu flex
50	11,0	-	Class 5	Aluminium flex

Extremely quiet, minimal vibration. Durable moulded body offering high resistance to wear and damage in all operating conditions. New Li-Ion 18V 2Ah High Power battery. The battery is equipped with LED indicators to show the remaining battery life at any time by pressing the adjacent button. Supplied in a robust plastic case to accommodate the tool and all the accessories. Two batteries and charger included. Operating temperature: -15 to +50 °C