

1:1

Series 320 – eSafe

- Vented safety function
- Extremely high flow capacity

eSafe Series 320 coupling is an easy-to-handle high performing coupling with a long service life. eSafe is a one hand operated safety coupling that vents before disconnection eliminating the risk of hose whip. Male threads on the couplings and nipples feature pre-applied thread sealant. The couplings have a smaller outside dimension than comparable designs. Full automatic operation ensures easy handling. eSafe complies with ISO Standard 4414 and EN 983.

Series 320 is also available in standard, Soft-Line and Multi-Link versions.

TECHNICAL DATA


Nominal flow diameter	7.6 mm (5/16")
Air flow	2250 l/min (79.4 CFM)
Max. working pressure	16 bar (232 PSI)
Min. burst pressure	140 bar (2030 PSI)
Temperature range	-20°C – +100°C (-4°F – +212°F)
Material coupling	Zinc-plated steel/brass
Material nipple	Hardened zinc-plated steel
Connection force	86 N
Markets	Global
Standards	CEJN Original, Eurostandard 7.4 mm

Flow capacity is measured at 6 bar (87 PSI) inlet pressure, and pressure drop at 0.5 bar (7 PSI).



CEJN Safety

AIR FLOW



Icon	Part No.	Connection
	HOSE CONNECTION 	10 320 2002 6.3 mm (1/4")
		10 320 2003 8 mm (5/16")
		10 320 2004 10 mm (3/8")
		10 320 2005 13 mm (1/2")
		10 320 2009 9 mm
	MALE THREAD 	10 320 2152 R 1/4"
		10 320 2154 R 3/8"
		10 320 2155 R 1/2"
		10 320 2452 NPT 1/4"
		10 320 2454 NPT 3/8"
	FEMALE THREAD 	10 320 2202 G 1/4"
		10 320 2204 G 3/8"
		10 320 2205 G 1/2"
		10 320 2402 NPT 1/4"
		10 320 2404 NPT 3/8"
STREAM-LINE CONNECTION 	10 320 2058 5 x 8 mm	
	10 320 2060 6.5 x 10 mm	
	10 320 2062 8 x 12 mm	
	10 320 2063 9.5 x 13.5 mm	
	10 320 2066 11 x 16 mm	
ESAFE SOFT-LINE COUPLING 	HOSE CONNECTION	10 320 2086 10 mm (3/8")
		10 320 2087 13 mm (1/2")
	STREAM-LINE CONNECTION	10 320 2080 6.5 x 10 mm
		10 320 2082 8 x 12 mm
		10 320 2085 11 x 16 mm
		10 320 2088 13 x 18 mm
	FEMALE THREAD	10 320 2232 G 1/4"
		10 320 2234 G 3/8"
		10 320 2434 NPT 3/8"

Icon	Part No.	Connection
	HOSE CONNECTION 	10 320 5001 5 mm (3/16")
		10 320 5002 6.3 mm (1/4")
		10 320 5003 8 mm (5/16")
		10 320 5009 9 mm
		10 320 5004 10 mm (3/8")
MALE THREAD 	10 320 5005 13 mm (1/2")	
	10 320 5151 R 1/8"	
	10 320 5152 R 1/4"	
	10 320 5154 R 3/8"	
	10 320 5155 R 1/2"	
FEMALE THREAD 	10 320 5263 G 1/4"	
	10 320 5264 G 3/8"	
	10 320 5265 G 1/2"	
	10 320 5451 NPT 1/8"	
	10 320 5452 NPT 1/4"	
STREAM-LINE CONNECTION 	10 320 5454 NPT 3/8"	
	10 320 5455 NPT 1/2"	
	10 320 5201 G 1/8"	
	10 320 5202 G 1/4"	
	10 320 5204 G 3/8"	
	10 320 5205 G 1/2"	
	10 320 5401 NPT 1/8"	
	10 320 5402 NPT 1/4"	
	10 320 5404 NPT 3/8"	
	10 320 5405 NPT 1/2"	
10 320 5058 5 x 8 mm		
10 320 5060 6.5 x 10 mm		
10 320 5062 8 x 12 mm		
10 320 5063 9.5 x 13.5 mm		
10 320 5066 11 x 16 mm		
10 320 5068 13 x 18 mm		

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, www.cejn.com, for general maintenance tips.