



# PUR Hose Kits – with Series 300

ARO 210 Standard

- Series 300 couplings and nipples
- Flexible PUR hose with long service life
- Pre-assembled and ready to use

CEJN Hose Kits come pre-assembled and ready for immediate use. They consist of an extremely flexible, straight braided or spiral polyurethane (PUR) hose combined with Series 300 Standard or Vented Safety couplings and nipples with reusable Stream-Line connections.

PUR Hose Kits are also available with Series 310, 320 and 410 Standard or Vented Safety couplings and nipples.



Flow capacity is measured at 6 bar (87 PSI) inlet pressure, and pressure drop at 0.5 bar (7 PSI).

		Service length	Part No.	ID x OD	Max working pressure
<b>SERIES 300</b>	Spiral	2.0 m	19 958 9977	5x8 mm	10 bar (145 PSI)
		4.0 m	19 958 9948	6.5x10 mm	10 bar (145 PSI)
		6.0 m	19 958 9952	6.5x10 mm	10 bar (145 PSI)
	Straight Braided	10.0 m	19 958 9802	8x12 mm	16 bar (232 PSI)
		15.0 m	19 958 9842	8x12 mm	16 bar (232 PSI)
<b>SERIES 300, ESAFE</b>	Spiral	2.0 m	19 958 9739	6.5x10 mm	10 bar (145 PSI)
			19 958 9330	8x12 mm	10 bar (145 PSI)
		4.0 m	19 958 9740	6.5x10 mm	10 bar (145 PSI)
			19 958 9712	8x12 mm	10 bar (145 PSI)
			19 958 9345	11x16 mm	10 bar (145 PSI)
		6.0 m	19 958 9741	6.5x10 mm	10 bar (145 PSI)
			19 958 9713	8x12 mm	10 bar (145 PSI)
	Straight Braided	8.0 m	19 958 9742	6.5x10 mm	10 bar (145 PSI)
			19 958 9714	8x12 mm	10 bar (145 PSI)
			19 958 9782	11 x 16 mm	10 bar (145 PSI)
		10.0 m	19 958 9704	8x12 mm	16 bar (232 PSI)
		15.0 m	19 958 9705	8x12 mm	16 bar (232 PSI)
		10.0 m	19 958 9335	9.5x13.5 mm	10 bar (145 PSI)
	15.0 m	19 958 9336	9.5x13.5 mm	10 bar (145 PSI)	



CEJN Safety

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, [www.cejn.com](http://www.cejn.com), for general maintenance tips.

## AIR FLOW

- HOSE 5X8 MM
- HOSE 6.5X10 MM
- HOSE 8X12 MM
- HOSE 9.5X13.5 MM
- HOSE 11X16 MM

